



ECOLOGIC Cleaner anti-moss

CLEANING PRODUCT BASED ON ENZYMES TO REMOVE AIRBORNE POLLUTION AS WELL AS GREEN AND BLACK ALGAE-ATTACK FROM ROOFS, WALLS, BALCONIES, ETC.

APPLICATION DATA

ECOLOGIC CLEANER can be applied on roof tiles, slates, masonry, rendering, pavement, concrete, wood, etc, to remove airborne pollution and green and black algae-attack.

CHARACTERISTICS

- * this method of cleaning is biological and durable and relies upon the use of enzymes
- * there are no chemical components to cause degradation/pollution of surface and groundwater
- * there is no corrosive attack on mineral substrates
- * it is ready for use

PRACTICE

Preparation :

- Remove thick moss deposits and crusts.
- The substrate is required to be dry.

Treatment :

- Liberally apply the ECOLOGIC CLEANER on the substrate with a watering can or brush.
- Allow time for the ECOLOGIC CLEANER to react.
- After a few days the algae-attack will disappear.
- In case of harsh pollution repeat the treatment as needed.

Consumption :

- Dependant upon on the porosity of the substrate and the severity of the pollution :
0,2 – 0,5 l/m²

Post treatment :

- In case of rendering or painting in the future with mineral products, the treated surface should be hosed with clean water ; do not use high pressure.

TECHNICAL DATA

Application temperature	5 to 25 °C
Tools	low pressure nozzle (Gloria nozzle), watering-can, brush, broom
Cleaning of tools	water
Dilution	ready mix, no dilution
Consumption	0,2 – 0,5 l/m ² (sample is needed)
Storage	6 months in original airtight recipient
Fire resistance classification	non-flammable
pH value by 20°C	10,5 +/- 0,5
Boiling temperature	100°C
Liquidity	higher than -5°C
Solubility	fully soluble in water
Active substance	enzyme complex
Appearance	green liquid, invisible drying
Package	jerry can of 1, 5 and 20 l
Odor	none





SAFETY PRECAUTIONS

Irritant for eyes and skin. Wear suitable protective clothing for application, as well as safety goggles and waterproof gloves. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. Cover glass, ceramic, metal and stone surfaces and window frames, which should not be overcoated with impermeable membranes. Stains should be removed immediately. Keep away from children. Dispose of the cans.



The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In every case, we recommend careful evaluation of the type of substrate and the climatic conditions before applying our products and that a test is undertaken to establish the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.

